

System details					Lamp details					
System ID	Total airflow (m ³ /h)	UV design location	Duct dimensions (mm)		Reference	Qty required	Total length (mm)	Power (W)	Power (W) @ 254nm	Minimum UVC dose (mj/cm ²)*
			Diameter Ø	Length						
430mmØ	250	round duct	430	1570	NNI 300/147 XL	1	1570	325	115	16,8
430mmØ	375	round duct	430	1570	NNI 300/147 XL	1	1570	325	115	11,2
430mmØ	500	round duct	430	1570	NNI 300/147 XL	1	1570	325	115	8,4
430mmØ	625	round duct	430	1570	NNI 300/147 XL	1	1570	325	115	6,7
690mmØ	500	round duct	690	1560	NNI 400/147 XL	1	1560	420	152	16,9
690mmØ	625	round duct	690	1560	NNI 400/147 XL	1	1560	420	152	13,5
690mmØ	750	round duct	690	1560	NNI 400/147 XL	1	1560	325	152	11,3
690mmØ	875	round duct	690	1560	NNI 400/147 XL	1	1560	325	152	9,7
690mmØ	1.000	round duct	690	1560	NNI 400/147 XL	1	1560	325	152	8,44
690mmØ	1.250	round duct	690	1560	NNI 400/147 XL	1	1560	325	152	6,75

* All lamps parallel to airflow

